REV.	DATE	DESCRIPTION
A	05/01/04	UPDATE DRAWING FORMAT



RECOMMENDED
MOUNTING HOLE





NOTES:
1. MAX. PANEL THICKNESS = 6.5mm

	DESCRIPTION	MATERIAL	FINISH	QTY
8				
7				
6				
5	HEX NUT	BRASS	SILVER	1
4	LOCK WASHER	BRASS	SILVER	1
3	GASKET	SILICONE	RED	1
2	CONTACT PIN	PHOS. BRONZE	GOLD	1
1	BODY	BRASS	SILVER	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 6mm ± 0.20mm
6 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	05/01/04
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/172/172124-10S.DWG

Amphenol Connex

PART DESCRIPTION
N FEMALE TO FEMALE BULKHEAD ADAPTOR

PART NO. 172124-10S

DWG. NO.	REV.	SIZE	SCALE
172124-10S.DWG	A	A	NA