

SPECIFICATION SHEET

JFW MODEL 75SA-095

SWITCH ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2150 MHz
Configuration	8 individually controlled 1P2T failsafe self-terminating electro-mechanical RF switches (port 1 is failsafe position)
Enclosure Type	Benchtop
Startup/Default States (configurable)	RF switches to port J1 at startup (see SWITCH command) DHCP enabled (see NET command) 4 Ethernet users (see NET command) Prompts off (see PROMPT command) All of these default settings can be changed by user. Unit can be configured for up to 12 Ethernet users.
Impedance	75 Ohms nominal
VSWR	1.6:1 maximum 1.4:1 typical
Insertion Loss	1.3 dB maximum 0.8 dB typical @ 2150 MHz
Isolation	50 dB minimum DC-1000 MHz 45 dB minimum 1000-2150 MHz 70 dB typical @ 1000 MHz 60 dB typical @ 2150 MHz
RF Input Power	+20 dBm
Switching Speed	10 milliseconds typical (after command is received and processed) (3 milliseconds typical processing time)
Manual Control	20-Button Keypad and LCD display (IP Address configurable via keypad) (Net mask configurable via keypad) (Gateway configurable via keypad) (Baud rate configurable via keypad)
Remote Control	Ethernet (DHCP, TCP/IP, 10/100, up to 12 users) RS-232 (up to 115200 Baud)

--CONTINUED--

SPECIFICATION SHEET

JFW MODEL 75SA-095

SWITCH ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Remote Commands

RF Switch Control Commands:
Switch, Set Switch, Read Switch, Set All Switches,
Read All Switches

System Commands:
Help, Identification, Store, Recall, Pause, Net,
Serial, Close, Disconnect, MOTD, Date, Message,
Restrict, IDENT, Name, Show Users, Reboot, Uptime,
Prompt

RF Connector

BNC, F or TNC female

AC Supply

100-240 VAC @ 47-63 Hz

Temperature Range

0°C to +50°C

Physical Size

See outline drawing 092-8385



ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	08/13/2015		TRS 08/13/2015				