

SPECIFICATION SHEET

**JFW MODEL 57ZT-1G AND 75ZT-1G
IMPEDANCE MATCHING TRANSFORMER**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 0.5-1000 MHz

Impedance 50 Ohms male / 75 Ohms female (57ZT)
75 Ohms male / 50 Ohms female (75ZT)

VSWR 1.3:1 maximum 0.5-3 MHz
1.2:1 maximum 3-300 MHz
1.3:1 maximum 300-1000 MHz

Attenuation Loss 0.75 dB maximum 0.5-300 MHz
1.2 dB maximum 300-1000 MHz

RF Input Power 1 Watt average

RF Connectors Available 50 Ohm Connectors:
BNC, SMA, N or TNC

Available 75 Ohm Connectors:
BNC, TNC, N, F or 1.6/5.6 (screw on)

Operating Temperature Range -20°C to +85°C

Storage Temperature Range -55°C to +125°C

Humidity (maximum) 95% relative humidity non-condensing

Outline Drawing Numbers 092-1069 (BNC)
092-2040 (N F-PM / N F)
092-1903 (N M / BNC F)
092-6243 (N M / F F)
092-7132 (N M / F M)
092-6422 (BNC M/BNC M)
092-8523 (SMA M/BNC F)
092-8570 (F M/TNC F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
14903	10/25/2007	E	TRS 10/25/2007	22232	12/11/2012	H	CLK 12/11/2012
18057	01/06/2009	F	SMR 01/06/2010	26214	01/19/2016	I	CLK 01/19/2016
22125	11/12/2012	G	BAC 11/12/2012	26368	03/04/2016	J	TRS 03/04/2016