

### Electrical Characteristics:

1. Characteristic Impedance:  $50 \Omega$
2. Frequency range: DC~4Ghz
3. Contact resistance  
Center conductor:  $\leq 6.0 \text{ m}\Omega$   
Out conductor:  $\leq 1.0 \text{ m}\Omega$
4. Insulation resistance:  $\geq 1000 \text{ M}\Omega$
5. Insulator withstanding: 750V
6. Durability: 500cycles

### 主要性能指标:

1. 特性阻抗:  $50 \Omega$
2. 频率范围: DC~4Ghz
3. 接触电阻:  
中心导体:  $\leq 6.0 \text{ m}\Omega$   
外导体:  $\leq 1.0 \text{ m}\Omega$
4. 绝缘电阻:  $\geq 1000 \text{ M}\Omega$
5. 介质耐压: 750V
6. 插拔次数: 500次

### Application: MIL-C-39012/68A



### 执行标准: MIL-C-39012/68A

### Material&Finishing

1. Center contact:  
Male: phosphor bronze, gold plated
2. Body: brass, gold plated
3. Insulators: PTFE

### 材料和镀层

1. 中心接触件:  
插针: 锡磷青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

 	SCALE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	2.5:1	
	NAME	
	DATE	
DRAWN		
CHECKED		
APPROVED		
SMB-JYHD RF COAXIAL CONNECTOR  <b>西安富士达科技股份有限公司</b> <b>XI'AN FORSTAR S&amp;T CO.,LTD.</b>		