



▾ SMD Isolator

Photo	Part No.	Center Frequency [MHz]	Frequency Range [MHz]	Band Width [MHz]	Insertion Loss [dB, Max]	Isolation [dB, Min]	VSWR [Max]	Power(F/R) [W, Max]	Size [mm]
	IL05BL(R)A836AAE	836.5	824 ~ 849	25	0.8	13	1.5	5.0/1.0	5 x 5 x 2.0T
	IL05BL(R)A881AAE	881.5	869 ~ 894	25	0.8	13	1.5	5.0/1.0	5 x 5 x 2.0T
	IL05BL(R)A902AAE	902.5	890 ~ 915	25	0.8	13	1.5	5.0/1.0	5 x 5 x 2.0T
	IL05BL(R)A947AAE	947.5	935 ~ 960	25	0.8	13	1.5	5.0/1.0	5 x 5 x 2.0T
	IL05AL(R)1765AAE	1765	1750 ~ 1780	30	0.6	15	1.5	10.0/2.0	5 x 5 x 2.0T
	IL05AL(R)1855AAE	1855	1840 ~ 1870	30	0.6	15	1.5	10.0/2.0	5 x 5 x 2.0T
	IL05AL(R)1880AAE	1880	1850 ~ 1910	60	0.6	15	1.5	10.0/2.0	5 x 5 x 2.0T
	IL05AL(R)1950AAE	1950	1920 ~ 1980	60	0.6	15	1.5	10.0/2.0	5 x 5 x 2.3T
	IL05AL(R)2140AAE	2140	2110 ~ 2170	60	0.6	15	1.5	10.0/2.0	5 x 5 x 2.3T
	IL05AL(R)2350AAE	2350	2300 ~ 2400	100	0.7	13	1.5	10.0/2.0	5 x 5 x 2.3T
	IL05AL(R)2450AAE	2450	2400 ~ 2500	100	0.7	12	1.5	10.0/2.0	5 x 5 x 2.3T
	IL05AL(R)2550AAE	2550	2500 ~ 2600	100	0.7	12	1.6	10.0/2.0	5 x 5 x 2.3T
	IL05AL(R)2650AAE	2650	2600 ~ 2700	100	0.7	13	1.5	10.0/2.0	5 x 5 x 2.3T
		IL07BL(R)0836AAE	836.5	824 ~ 849	25	0.65	15	1.5	10.0/2.0
IL07BL(R)0881AAE		881.5	869 ~ 894	25	0.65	15	1.5	10.0/2.0	7 x 7 x 2.0T
IL07BL(R)0902AAE		902.5	890 ~ 915	25	0.65	15	1.5	10.0/2.0	7 x 7 x 2.0T
IL07BL(R)0942AAE		942.5	925 ~ 960	35	0.65	13	1.5	10.0/2.0	7 x 7 x 2.0T
IL07BL(R)1842AAE		1842.5	1805 ~ 1880	75	0.6	15	1.5	10.0/2.0	7 x 7 x 2.5T
IL07BL(R)1880AAE		1880	1850 ~ 1910	60	0.6	15	1.5	10.0/2.0	7 x 7 x 2.5T
IL07BL(R)1950AAE		1950	1920 ~ 1980	60	0.6	15	1.5	10.0/2.0	7 x 7 x 2.5T
IL07BL(R)2140AAE		2140	2110 ~ 2170	60	0.6	15	1.5	10.0/2.0	7 x 7 x 2.5T