


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 4.9–5.8 GHz
 Insertion Loss: 0.6dB Max.
 Isolation: 18dB Min.
 VSWR: 1.35:1 Max.
 Phase balance: ±6 Deg. Max.
 Amplitude balance: ±0.4dB Max.
 Power: 30 Watts (Load vswr@1.2)

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
			UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.015 ANGLE: ±1/2°	DRAWING TITLE:		SHEET:
			PART NO.		4-WAY POWER DIVIDER	
			CAGE CODE:		PS4-217	
DRAWN:	DATE:	PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	SIZE:	REV:	DWG NO.	
APPROVED:	DATE:		OD2L5	A	N/A	85078
			DO NOT SCALE THE DRAWING			