SPECIFICATION SHEET

JFW MODEL 50MS-337

24 X 4 BLOCKING SOLID STATE MATRIX SWITCH

JFW Industries, Inc. Phone: 317-887-1340 sales@jfwindustries.com www.jfwindustries.com

Frequency Range 700-3000 MHz

Configuration 24 x 4 Blocking Matrix

(Unused Input Ports self-terminating)
(Unused Output Ports self-terminating)

(all ports are bi-directional)

(the ADMIN password is located on rear panel)

Startup/Default States

(configurable)

All ports off at startup (see SWITCH STARTUP command)

DHCP enabled (see NET command)

4 Ethernet users (see NET USERS command)

Prompts off (see PROMPT command)

Enclosure Type 19 inch rack mount @ 7RU high

Impedance 50 Ohms nominal

VSWR 1.6:1 typical / 1.8:1 maximum

Insertion Loss 5 dB typical @ 700 MHz 8 dB typical @ 3000 MHz

Isolation Input to Input:

70dB typical / 50 dB minimum

Output to Output:

75dB typical / 65 dB minimum

Input to Output:

100 dB typical / 90dB minimum

RF Input Power +20 dBm average

Switching Speed 15 microseconds

(after command is received and processed)
(3 milliseconds typical processing time)

AC Supply 100-240 VAC @ 47-63 Hz

4 Amp 5x20mm "Slo-Blo" AC fuse Littelfuse #215-004, JFW #025-018

Manual Control 20-Button Keypad and LCD display

(IP Address configurable via keypad) (Net mask configurable via keypad) (Gateway configurable via keypad) (Baud rate configurable via keypad)

Remote Control Ethernet (DHCP, TCP/IP, 10/100, up to 12 users)

RS-232 (up to 115200 Baud)

--CONTINUED--

Page 1 of 2 JFW FORM E-7-F REV F

SPECIFICATION SHEET

JFW MODEL 50MS-337

24 X 4 BLOCKING SOLID STATE MATRIX SWITCH

JFW Industries, Inc. Phone: 317-887-1340 sales@jfwindustries.com www.jfwindustries.com

Remote Commands Matrix Commands:

Set Output, Read Output, Read All Outputs

System Commands:

Help, Identification, Store, Recall, Pause, Net, Serial, Close, Disconnect, MOTD, Date, Message, Restrict, IDENT, Name, Show Users, Reboot, Uptime,

Prompt

RF Connector N, SMA or TNC female

Operating Temperature Range 0°C to +50°C

Physical Size See outline drawing 092-8175



Page 2 of 2 JFW FORM E-7-F REV F