


剥线尺寸  
stripping dimension



产品型号 type	配接电缆 cable type
L29-KFB3	SFT-50-3-1、RG402/U

**Electrical Characteristics:**

1. Characteristic Impedance: 50  $\Omega$
2. Frequency range: DC~7.5Ghz
3. Contact resistance  
Center conductor:  $\leq 1.0 \text{ m}\Omega$   
Out conductor:  $\leq 0.5 \text{ m}\Omega$
4. Insulation resistance:  $\geq 10000 \text{ M}\Omega$
5. Insulator withstanding: 4000V
6. VSWR:  $\leq 1.5$
7. Durability: 500cycles

**主要性能指标:**

1. 特性阻抗: 50  $\Omega$
2. 频率范围: DC~7.5Ghz
3. 接触电阻:  
中心导体:  $\leq 1.0 \text{ m}\Omega$   
外导体:  $\leq 0.5 \text{ m}\Omega$
4. 绝缘电阻:  $\geq 10000 \text{ M}\Omega$
5. 介质耐压: 4000V
6. 电压驻波比:  $\leq 1.5$
7. 插拔次数: 500次

**Application: IEC 60169-4**



**执行标准: IEC 60169-4**

**Material & Finishing**

1. Center contact :  
Female: phosphor bronze, silver plated
2. Bodies: brass, silver plated
3. Insulators: PTFE

**材料和镀层**

1. 中心接触件:  
插孔: 锡磷青铜, 镀银
2. 壳体: 黄铜, 镀银
3. 绝缘子: 聚四氟乙烯

 	SCALE
	1.5:1
NAME	DATE
DRAWN	
CHECKED	
APPROVED	

L29-KFB3  
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE mm, TOLERANCES ARE  
FRACTIONS DECIMALS ANGLES  
.X $\pm$  .15  $\pm 1^\circ$   
.XX $\pm$  .05  
.XXX $\pm$

西安富士达科技股份有限公司  
XI'AN FORSTAR S&T CO., LTD.