



2 dB Fixed Attenuator, N Male To N Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz

TECHNICAL DATA SHEET

PE7017-2

Configuration

Design	Fixed, Bidirectional Attenuator
Connector 1	N Male
Connector 2	N Female
Body Material and Plating	Black Anodized Aluminum Heatsink

Electrical Specifications * Values at 25°C, sea level

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Impedance		50		Ohms
Attenuation Value		2		dB
Input Power			25	Watts
VSWR			1.4:1	

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Range	DC to 18					GHz
VSWR	1.4:1					
Attenuation Accuracy	± 0.8					dB

Mechanical Specifications

Size	
Length	4.5 in [114.3 mm]
Width	2.65 in [67.31 mm]
Height	2.65 in [67.31 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 dB Fixed Attenuator, N Male To N Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz PE7017-2](#)



2 dB Fixed Attenuator, N Male To N Female Black Anodized
Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz

TECHNICAL DATA SHEET

PE7017-2

Connectors

Description	Connector 1	Connector 2
Type	N Male	N Female
Connector Specification	MIL-STD-348	MIL-STD-348
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Coupling Nut Material and Plating	Passivated Stainless Steel	
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)
RoHS Compliant

Plotted and Other Data

Notes:

- Values at 25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 dB Fixed Attenuator, N Male To N Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz PE7017-2](#)




2 dB Fixed Attenuator, N Male To N Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz

TECHNICAL DATA SHEET

PE7017-2

Outline Drawing



2 dB Fixed Attenuator, N Male To N Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 dB Fixed Attenuator, N Male To N Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz PE7017-2](http://www.pasternack.com/2db-fixed-n-female-n-male-25-watts-attenuator-pe7017-2-p.aspx)

URL: <http://www.pasternack.com/2db-fixed-n-female-n-male-25-watts-attenuator-pe7017-2-p.aspx>