





TECHNICAL DATA SHEET

PE7367-6

6 dB Fixed Attenuator, N Male To N Female Rated To 25 Watts Up To 18 GHz

Configuration

Design Fixed, Bidirectional Attenuator

Connector 1 N Male
Connector 2 N Female

Body Material and Plating Aluminum Heatsink, Black Anodized

Electrical Specifications

Frequency Range, GHz DC to 18
Impedance, Ohms 50
Attenuation Value, dB 6 to 6
Maximum Input Power, Watts 25
Maximum VSWR 1.6:1

Frequency 1

Range, GHz
Insertion Loss, dB
VSWR
1.3:1
Attenuation Accuracy, dB
Maximum Input Power, Watts
DC to 6
6
0.5
25

Frequency 2

Range, GHz 6 to 12.4 VSWR 1.45:1 Attenuation Accuracy, dB 0.75

Frequency 3

Range, GHz 12.4 to 18 VSWR 1.6:1
Attenuation Accuracy, dB 1

Mechanical Specifications

Temperature

Operating Range, deg C -55 to +125

Size

 Length, in [mm]
 4.5 [114.3]

 Width, in [mm]
 2.41 [61.21]

 Weight, lbs [g]
 0.8 [362.87]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 6 dB Fixed Attenuator, N Male To N Female Rated To 25 Watts Up To 18 GHz PE7367-6

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered



6 dB Fixed Attenuator, N Male To N Female Rated To 25 Watts Up To 18 GHz



TECHNICAL DATA SHEET

PE7367-6

Connector 1

Type N Male
Contact Material and Plating Brass, Gold
Contact Plating Specification Silver
Hex Size, In. 11/16

Body Material and Plating Stainless Steel, Passivated

Body Plating Specification Passivated

Connector 2

Type N Female
Contact Material and Plating Brass, Gold
Outer Conductor Material and Plating Brass, Silver

Hex Size, In. 11/16

Body Material and Plating Stainless Steel, Passivated

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/6db-fixed-n-male-n-female-25-watts-attenuator-pe7367-6-p.aspx

6 dB Fixed Attenuator, N Male To N Female Rated To 25 Watts Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



ISO 9001: 2008 Registered

PE7367-6 CAD Drawing

6 dB Fixed Attenuator, N Male To N Female Rated To 25 Watts Up To 18 GHz

