

SPECIFICATION SHEET

JFW MODEL 50T-410

TERMINATION

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-4000 MHz

Impedance 50 Ohms nominal

VSWR 1.15:1 maximum

RF Input Power 5 Watts average @ 25°C

Peak Power 1000 Watts (1 microsecond)

RF Connector BNC, N, SMA, TNC or reverse polarity TNC (male or female)

Operating Temperature Range -40°C to +85°C

Physical Size See outline drawings:

- 092-4403-01 (SMA male)
- 092-4403-02 (SMA female)
- 092-4403-03 (BNC male)
- 092-4403-04 (BNC female)
- 092-4403-05 (TNC male)
- 092-4403-06 (TNC female)
- 092-4403-07 (N male)
- 092-4403-08 (N female)
- 092-4403-09 (Rev. Polarity TNC male)
- 092-4403-10 (Rev. Polarity TNC female)

| ECR/ECN # | DATE | REV | APPR / DATE | ECR/ECN # | DATE | REV | APPR / DATE |
|-----------|------------|-----|----------------|-----------|------|-----|-------------|
| | 02/13/2004 | | TRS 02/13/2004 | | | | |
| 4698 | 10/06/2004 | A | CLV 10/06/2004 | | | | |
| 20855 | 11/04/2011 | B | TRS 11/04/2011 | | | | |