



产品型号 type	L	L1	L2	L3	h
SMA-KFD34	10.5	1.0	1.0	1.0	0.4
SMA-KFD305	13.6	4	2.5	0	0.2

Electrical Characteristics:

1. Characteristic Impedance: 50 Ω
2. Frequency range: DC~18Ghz
3. Contact resistance
Center conductor: ≤3.0 mΩ
Out conductor: ≤2.0 mΩ
4. Insulation resistance: ≥5000MΩ
5. Insulator withstanding: 1000V
6. Durability: 500cycles

主要性能指标:

1. 特性阻抗: 50 Ω
2. 频率范围: DC~18Ghz
3. 接触电阻:
中心导体: ≤3.0 mΩ
外导体: ≤2.0 mΩ
4. 绝缘电阻: ≥5000MΩ
5. 介质耐压: 1000V
6. 插拔次数: 500次

Application: MIL-C-39012/55D

执行标准: MIL-C-39012/55D

Material&Finishing

1. Center contact :
Female: beryllium, gold plated
2. Body: Brass, gold plated
3. Insulators: PTFE

材料和镀层

1. 中心接触件:
插孔: 铍青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

	SCALE	SMA-KFD34 RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	2.5:1		
NAME	DATE		
DRAWN			
CHECKED			
APPROVED			