



10 dB Fixed Attenuator, 2.92mm Male To
2.92mm Female Passivated Stainless Steel
Body Rated To 0.5 Watts Up To 40 GHz

TECHNICAL DATA SHEET

PE7046-10

10 dB Fixed Attenuator, 2.92mm Male To 2.92mm Female Passivated Stainless Steel Body Rated To 0.5 Watts Up To 40 GHz

Configuration

Design	Fixed, Bidirectional Attenuator
Connector 1	2.92mm Male
Connector 2	2.92mm Female

Electrical Specifications

Frequency Range, GHz	DC to 40
Impedance, Ohms	50
Attenuation Value, dB	10
Maximum Input Power, Watts	0.5
Maximum VSWR	1.4:1

Frequency 1

Range, GHz	DC to 40
Attenuation Accuracy, dB	± 1

Mechanical Specifications

Size

Length, in [mm]	0.85 [21.59]
Width, in [mm]	0.312 [7.92]

Connector 1

Type	2.92mm Male
Hex Size, in.	5/16
Torque, in-lbs [Nm]	8 [0.9]

Connector 2

Type	2.92mm Female
------	---------------

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, 2.92mm Male To 2.92mm Female Passivated Stainless Steel Body Rated To 0.5 Watts Up To 40 GHz PE7046-10](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



10 dB Fixed Attenuator, 2.92mm Male To
2.92mm Female Passivated Stainless Steel
Body Rated To 0.5 Watts Up To 40 GHz

TECHNICAL DATA SHEET

PE7046-10

Plotted and Other Data

Notes:

Values at 25 °C, sea level

10 dB Fixed Attenuator, 2.92mm Male To 2.92mm Female Passivated Stainless Steel Body Rated To 0.5 Watts Up To 40 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, 2.92mm Male To 2.92mm Female Passivated Stainless Steel Body Rated To 0.5 Watts Up To 40 GHz PE7046-10](http://www.pasternack.com/10db-fixed-2.92mm-male-2.92mm-female-0.5-watts-attenuator-pe7046-10-p.aspx)


URL: <http://www.pasternack.com/10db-fixed-2.92mm-male-2.92mm-female-0.5-watts-attenuator-pe7046-10-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE7046-10 CAD Drawing

10 dB Fixed Attenuator, 2.92mm Male To 2.92mm Female Passivated
Stainless Steel Body Rated To 0.5 Watts Up To 40 GHz

P/N	ATTEN.	FIGURE
PE7046-1	1 dB	1
PE7046-2	2 dB	1
PE7046-3	3 dB	1
PE7046-6	6 dB	1
PE7046-10	10 dB	1
PE7046-20	20 dB	1
PE7046-30	30 dB	1



2.92mm FEMALE

FIGURE 1

2.29mm MALE

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE7046

FSCM NO. 53919

CAD FILE 020113

SCALE N/A

SIZE A

2231

PE PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com