


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



**SPECIFICATIONS**

Frequency Range: 10.9–12.75 GHz  
 Insertion Loss: 1.25dB Max.  
 Isolation: 16dB Min.  
 VSWR: 1.65:1 Max.  
 Phase Balance: ±10 Deg. Max.  
 Amplitude Balance: ±0.6dB Max.  
 Power: 20W (Load vswr@1.2)

MATERIAL:		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
			SHEET:	N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°	DRAWING TITLE: <b>3-WAY POWER DIVIDER</b>	
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	PART NO. <b>PS3-60</b>	
DRAWN:	DATE:	THIRD ANGLE PROJECTION 	CAGE CODE:	DWG. NO.
Paiboon Luekhamhan	06-08-1999		OD2L5	81313
APPROVED:	DATE:	SIZE: A	REV: N/A	
T. Nguyen	06-08-1999	DO NOT SCALE THE DRAWING		