

**SPECIFICATION SHEET**

**JFW MODEL 50S-1785**

**1P8T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Frequency Range	0.5-18 GHz
Configuration	1P8T Self Terminating
Impedance	50 Ohms nominal
VSWR	1.4:1 typical 0.5-4GHz 1.7:1 typical 4-18GHz 2.0:1 maximum 0.5-18GHz
Insertion Loss	3.3 dB typical 0.5-8GHz 4.5 dB typical 8-18GHz 5.0 dB maximum 0.5-18GHz
Isolation	90 dB typical 0.5-8GHz 80 dB typical 8-18GHz 65 dB minimum 0.5-18GHz
Switching Speed (50% TTL to 10% or 90% RF)	100 nanoseconds maximum 75 nanoseconds typical
RF Input Power	+27 dBm maximum
3rd Order Intercept Point	+45dBm minimum
Control Logic (8 Lines) (1 line per port)	TTL "Low" (0-0.8V) for Insertion Loss (only one port active at a time)  TTL "High" (2.0-5.0V) for OFF and Terminated
DC Supplies	+5 ±0.3 Vdc @ 320 mA nominal and -12 to -15 Vdc @ 40 mA nominal
DC Connector	Solder Terminals
RF Connector	SMA female
Operating Temperature Range	-55°C to +85°C
Storage Temperature Range	-65°C to +125°C
Weight	60 grams nominal
Physical Size	See outline drawing 092-8415

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/14/2015		BAC 09/14/2015				
26492	03/29/2016	A	BAC 03/29/2016				