



No.	Revision	Date	Sign
▲			
▲			

N ST PLUG  
(Anti-torque)  
Coupling/Brass-Nickel  
Body/Brass-Nickel

CABLE: SEMI RIGID  
SR -250

Length ±0.05INCH

P/N	L (inch)	P/N	L (inch)	P/N	L (inch)
-02	2	-14	14	-26	26
-03	3	-15	15	-27	27
-04	4	-16	16	-28	28
-05	5	-17	17	-29	29
-06	6	-18	18	-30	30
-07	7	-19	19	-31	31
-08	8	-20	20	-32	32
-09	9	-21	21	-33	33
-10	10	-22	22	-34	34
-11	11	-23	23	-35	35
-12	12	-24	24	-36	36
-13	13	-25	25		

NO.	DESCRIPTION	Q'TY	PART NO.	REMARKS.
4	Marking tube	1	GSHS-1625G	White
3	Bonding tube	2	GSHS-3625W	Black-12mm
2	COAX CABLE	1	SR-250	
1	CONNECTOR(N-SP)	2	1N-103-AT01	
PARTS No. CA-5000-16-XX		NAME RF-CABLE ASSY		APPROVED S.K
		TOLERANCES OTHERWISE SPEC. ±0.05 ANGLES ±1°		CHECKED
		SCALE N/S	UNIT mm	DESIGNED T.P
		DWG NO. CA-5000-16-XX		DATE. 8/11/08

CUSTOMER

