



Specifications

Parameter	Minimum	Typical *	Maximum
Frequency Range (MHz)	698		806
Insertion Loss (dB)		< .30	.40
Isolation (dB)	20	> 23	
Return Loss (dB)	20	> 23	

^{*} Typical Values Represent Mid-Band Performance @ +23 °C.

Power & Temperature Ratings

Parameter	Maximum
Forward PWR Peak/AVG	1000/200 Watts
Reverse Power CW	200 Watts
Operating Temperature	-20 to +85° C
Storage Temperature	-40 to +95° C

CW CIRCULATOR MODEL: RFCR2129

UNLESS OTHERWISE SPECIFIED THIRD ANGLE PROJECTION ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]: ⇎ \bigoplus TOLERANCES ARE: RFCI 1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° **APPROVALS** DATE 2 PLACE DECIMAL ±.10 [±.004] SURFACE ROUGHNESS 16/ REMOVE ALL BURRS AND BREAK SHARP EDGES. DRAWN BY: ΗV 04/08/13 SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5 CHECKED BY: P.T 04/10/13 PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT DESIGN BY: P.T 11/14/12 OUTLINE/SPECS IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RE CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO ENGINEER BY: P.T 04/12/13 L.T 4/12/13 SIZE CAGE NO. DWG NO. REV. DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL." 1 CR2129-OS Α PROG. MGMT/MKT DO NOT SCALE DRAWING SHEET 1 OF 1 SCALE: FULL