

Coaxial

Voltage Controlled Oscillator

ZX95-200+

Linear Tuning 100 to 200 MHz

Features

- excellent harmonic suppression
- low phase noise
- octave bandwidth
- low pushing & pulling
- linear tuning
- protected by US patent 6,790,049



CASE STYLE: GB956

Connectors	Model	Price	Qty.
SMA	ZX95-200-S+	\$37.95 ea.	(1-9)

Applications

- R & D
- lab
- instrumentation
- test equipment

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications


MODEL NO.	FREQ. (MHz)		POWER OUTPUT (dBm)	PHASE NOISE dBc/Hz SSB at offset frequencies, kHz				TUNING				NON HARMONIC SPURIOUS (dBc)	HARMONICS (dBc)		PULLING pk-pk @ 12 dB (MHz)	PUSHING (MHz/V)	DC OPERATING POWER		
	Min.	Max.		Typ.	1	10	100	1000	VOLTAGE RANGE (V)	SENSI- TIVITY (MHz/V)	PORT CAP (pF)		3 dB MODULATION BANDWIDTH (MHz)	Typ.			Typ.	Max.	Typ.
ZX95-200+	100	200	+10	-86	-106	-128	-148	1	17	7-10	540	0.12	-90	-30	-20	0.5	0.2	12	20

Maximum Ratings

Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Max. Supply Voltage (Vcc)	13V
Absolute Max. Tuning Voltage (Vtune)	18V
All specifications	50 ohm system

Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt.
1.20	.75	.46	1.18	.04	.38	.38	.57	.18	.33	.21	.22	.18	1.00	.50	.35	.18	.106	grams
30.48	19.05	11.68	29.97	1.02	9.65	9.65	14.48	4.57	8.38	5.33	5.59	4.57	25.40	12.70	8.89	4.57	2.69	35.0



For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.


REV. B
M108294
EDR-6293
ZX95-200+
RAV/URJ
120830
Page 1 of 2

Performance Data & Curves*

ZX95-200+

V TUNE	TUNE SENS (MHz/V)	FREQUENCY (MHz)			POWER OUTPUT (dBm)			Icc (mA)	HARMONICS (dBc)			FREQ. PUSH (MHz/V)	FREQ. PULL (MHz)	PHASE NOISE (dBc/Hz) at offsets				FREQ OFFSET (KHz)	PHASE NOISE at 150 MHz (dBc/Hz)
		-55°C	+25°C	+85°C	-55°C	+25°C	+85°C		F2	F3	F4			1kHz	10kHz	100kHz	1MHz		
0.00	11.08	86.2	83.1	82.7	6.62	5.88	4.63	15.52	-27.6	-46.4	-44.0	0.05	0.04	-85.5	-104.0	-125.4	-146.2	1.0	-87.0
0.50	9.82	91.9	88.6	88.5	7.58	7.30	6.32	15.52	-27.8	-47.6	-45.6	0.35	0.05	-86.1	-107.1	-127.8	-148.2	2.0	-93.72
1.00	8.23	96.5	93.5	93.4	8.53	8.55	7.83	15.45	-28.0	-49.6	-46.8	0.25	0.08	-88.0	-108.9	-129.3	-149.2	3.5	-96.56
1.50	7.40	100.4	97.6	97.5	9.28	9.55	9.05	15.39	-29.5	-51.8	-48.6	0.19	0.13	-87.9	-110.1	-129.8	-150.3	6.0	-102.44
2.00	6.99	104.0	101.3	101.2	9.59	9.87	9.48	15.34	-34.0	-48.6	-49.5	0.17	0.13	-87.3	-108.4	-130.4	-151.2	8.5	-104.48
3.00	6.67	110.8	108.2	108.0	9.85	10.13	9.83	15.26	-39.0	-44.8	-51.0	0.16	0.16	-88.6	-110.3	-130.8	-151.4	10.0	-106.44
4.00	6.75	117.4	114.9	114.6	9.94	10.22	9.97	15.19	-33.0	-43.3	-51.0	0.14	0.20	-88.1	-110.4	-130.6	-151.1	24.9	-115.02
5.00	7.09	124.2	121.7	121.3	9.98	10.24	10.02	15.12	-29.7	-41.8	-51.1	0.14	0.27	-86.5	-109.4	-130.1	-150.7	35.5	-117.64
6.00	7.59	131.4	128.9	128.4	9.99	10.22	10.01	15.05	-27.9	-40.7	-50.7	0.14	0.38	-85.3	-108.1	-129.3	-149.8	60.7	-122.81
7.00	8.10	139.1	136.6	136.0	10.00	10.18	9.97	14.99	-27.5	-39.8	-51.0	0.16	0.44	-86.8	-108.2	-128.6	-149.0	86.7	-126.16
8.00	8.53	147.3	144.8	144.2	9.98	10.11	9.90	14.93	-27.5	-39.3	-51.6	0.20	0.40	-87.3	-106.8	-127.7	-149.0	100.0	-127.33
9.00	8.82	155.9	153.4	152.8	9.93	10.00	9.78	14.88	-28.5	-38.6	-53.4	0.24	0.41	-83.9	-105.5	-127.2	-148.0	148.1	-131.14
10.00	8.93	164.7	162.3	161.6	9.84	9.84	9.62	14.83	-29.5	-38.1	-55.7	0.26	0.57	-84.3	-106.0	-126.4	-147.4	211.6	-134.78
11.00	9.19	173.6	171.3	170.5	9.73	9.67	9.44	14.80	-30.3	-37.4	-56.7	0.27	0.48	-84.0	-105.7	-125.8	-146.6	361.5	-139.44
12.00	9.41	182.7	180.5	179.7	9.57	9.47	9.23	14.76	-31.4	-37.2	-56.8	0.23	0.40	-82.4	-103.7	-125.1	-145.8	432.2	-141.01
13.00	9.81	192.1	190.0	189.2	9.38	9.24	8.99	14.73	-32.1	-37.2	-55.4	0.23	0.37	-84.0	-103.9	-124.1	-144.8	507.5	-142.59
14.00	10.16	202.0	199.9	199.1	9.14	8.98	8.71	14.71	-32.5	-36.9	-52.1	0.26	0.48	-82.2	-102.8	-123.0	-143.5	600.0	-143.97
15.00	10.29	212.1	210.1	209.3	8.89	8.69	8.40	14.69	-30.7	-36.3	-49.5	0.35	0.56	-81.1	-101.6	-121.2	-142.6	712.4	-145.36
16.00	10.03	222.4	220.4	219.5	8.58	8.38	8.06	14.68	-29.5	-36.8	-48.9	0.46	0.67	-80.6	-100.0	-120.5	-141.5	851.6	-147.21
17.00	9.72	232.3	230.2	229.3	8.27	8.08	7.72	14.67	-28.2	-37.2	-49.6	0.55	0.74	-79.2	-98.8	-119.6	-139.7	1000.0	-148.36

*at 25°C unless mentioned otherwise



For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.