

8.5 to 11.5GHz – Microstrip Isolator

Design Features


- ◆ Can be dual junction even three for high isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics

Model Number	Freq. Range (GHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYMI615A85T95	8.5 ~ 9.5	0.5	20	1.25	10	3	Microstrip	-55 ~ +85
UIYMI615A9T10	9.0 ~ 10.0	0.5	20	1.25	10	3	Microstrip	-55 ~ +85
UIYMI615A95T105	9.5 ~ 10.5	0.5	20	1.25	10	3	Microstrip	-55 ~ +85
UIYMI615A9T11	9.0 ~ 11.0	0.5	18	1.3	10	3	Microstrip	-55 ~ +85
UIYMI615A105T115	10.5 ~ 11.5	0.5	20	1.25	10	3	Microstrip	-55 ~ +85

- 2 List are specify frequency range and other ranges available.
 2 Please enter below information when inquiry and mark * is must.
 * 1. The specific frequency range
 * 2. Power handling (Forward, Reverse, Peak, etc.)
 * 3. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±0.2mm unless otherwise stated.

Ver. 5

A2-5G, Zhujiang Plaza, Longxiang Blvd, Longgang District, Shenzhen 518172, China.

Tel: +86-755-25999990 25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com Web: www.uiy.com