

SPECIFICATION SHEET
JFW MODEL 75DR-026
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

| | |
|-----------------------------|---|
| Frequency Range | DC-1500 MHz |
| Impedance | 75 Ohms nominal |
| Attenuation Range | 0-50 dB in 1 dB steps |
| VSWR | 1.5:1 maximum |
| Insertion Loss | 1.0 dB maximum 0.5 dB typical |
| Attenuation Accuracy | ± 0.5 dB or 3% (whichever is greater) |
| RF Input Power | 1 Watt average 1000 Watts peak |
| Direction of Rotation | Attenuation increases in a Clockwise direction |
| Indexing | 30 degrees with stops at minimum and maximum |
| RF Connector | BNC, F, or N female |
| Operating Temperature Range | -20°C to +85°C |
| Knob/Panel Mounting Drawing | 092-8435-02 |
| Outline Drawings | 092-327-06 (75DR-026 N) 092-1513-06 (75DR-026 BNC) 092-7445-02 (75DR-026 F) |

| ECR/ECN # | DATE | REV | APPR / DATE | ECR/ECN # | DATE | REV | APPR / DATE |
|-----------|------------|-----|----------------|-----------|------|-----|-------------|
| | 04/19/2013 | | TRS 04/19/2013 | | | | |
| 25776 | 09/29/2015 | A | TRS 09/29/2015 | | | | |