

## 180 to 300MHz – Coaxial Isolator

### Design Features


- ◆ Can be dual junction even three for high isolation.
- ◆ Military, space and commercial applications.
- ◆ Guaranteed for one year standard.
- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.

### RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYCI5257A180T200NF	180 ~ 200	0.7	18	1.3	300	30	N-F	-20 ~ +65
UIYCI5257A192T232SF	192 ~ 232	0.8	18	1.3	100	30	SMA-F	0 ~ +65
UIYCI5257A1975T2075NF	197.5 ~ 207.5	0.6	20	1.25	300	30	N-F	-20 ~ +65
UIYCI5257A200T210NFTTAB	200 ~ 210	0.5	20	1.25	300	30	N-F to TAB	-20 ~ +65
UIYCI5257A210T250SF	210 ~ 250	0.8	18	1.3	100	30	SMA-F	-20 ~ +65
UIYCI5257A250T280SM	250 ~ 280	0.5	20	1.25	100	30	SMA-M	-20 ~ +65
UIYCI5257A265T275SF	265 ~ 275	0.4	20	1.2	100	30	SMA-F	-30 ~ +70

- <sup>2</sup> List are specify frequency range and other ranges available.  
<sup>2</sup> Please enter below information when inquiry and mark \* is must.
- \* 1. The specific frequency range
  - \* 2. Power handling (Forward, Reverse, Peak, etc.)
  - \* 3. Connect type (SMA Male/ Female, N Male/ Female, etc.)
  - 4. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

### Mechanical Drawing



Unit: mm/ inch, General part tolerance is  $\pm 0.2$ mm unless otherwise stated.

Ver. 5

A2-5G, Zhujiang Plaza, Longxiang Blvd, Longgang District, Shenzhen 518172, China.

Tel: +86-755-25999990 25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com Web: www.uiy.com