



ZONE		REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

Frequency Range: 2.60-3.95 GHz  
 Waveguide Size: WR284 (Input)  
 Flange Types: Per Order (-1,-2,-6,-7,-S)  
 VSWR: 1.15 Max.  
 Average Power: 5000 Watts

**F = FLANGE TYPES**

- 1 = CPRG
- 2 = CPRF
- 6 = UG-COVER
- 7 = UG-CHOKE
- S = SPECIAL

FLANGE TYPE PER ORDER (WR284 UG-COVER SHOWN)

**ORDERING INFORMATION**

EXAMPLE PART NUMBER: WL-4-F  
 VERY HIGH POWER SERIES  
 FREQUENCY BAND  
 FLANGE TYPE

Aluminum 6061 High Temp. Black Paint		<b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES, INC. 10000 WILSON BLVD., SUITE 100 FORT WORTH, TEXAS 76154 TEL: (817) 441-8888 FAX: (817) 381-0116 <a href="http://www.mcli.com">www.mcli.com</a>		FINISH: N/A TOLERANCE: N/A
UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN INCHES OR (mm) DIMENSIONS IN MILLIMETERS DECIMALS: 2 1/100 DECIMALS: 3 1/1000 ANGLES: 1/2°		ORDER NO.: WL-4-F TITLE: TERMINATION, WR284 5000 Watts		
DESIGNED: Pulboon Luthmashan DATE: 05-03-2011	DRAWN: T. Nguyen DATE: 05-03-2011	QUANTITY: 002L5	PART NO.: 85653	