

SPECIFICATION SHEET
JFW MODEL 50S-1887
1P2T SOLID STATE RF SWITCH

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	225-400 MHz
Configuration	1P2T
Impedance	50 Ohms nominal
VSWR	1.15:1 typical 1.30:1 maximum
Insertion Loss	0.3 dB typical 0.5 dB maximum
Isolation	55 dB typical 45 dB minimum
Switching Speed	10 microseconds maximum (50% TTL to 10% or 90% RF)
RF Input Power	100 Watts average (Cold switch) 500 Watts peak (1 usec pulse) 20 Watts average (Hot switch)
Control Logic (1 Line)	TTL "Low" (0-0.8V) for common to J1 TTL "High" (2.0-5.0V) for common to J2
DC Supply	+15 Vdc @ 250 mA nominal and +5 Vdc @ 50 mA nominal
RF Connector	Plug-in Printed Circuit or SMT
DC Connector	Plug-in Printed Circuit or SMT
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	-55°C to +85°C
Physical Size	See outline drawing 092-6633 (PC) 092-6682 (SMT)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	07/08/2010		BAC 07/08/2010				
18983	08/09/2010	A	BAC 08/09/2010				