# **RF Transformer**

T36-1-KK81+ T36-1-KK81

 $50\Omega$ 

0.03 to 20 MHz


# **Maximum Ratings**

Operating Temperature	-20°C to 85°C		
Storage Temperature	-55°C to 100°C		
RF Power	0.25W		
DC Current	30mA		
Pormonant damage may occur if any	of those limits are evenedo		

### **Pin Connections**


PRIMARY DOT	4
PRIMARY	6
SECONDARY DOT	3
SECONDARY	1
SECONDARY CT	_
NOT USED	2,5

## **Outline Drawing**



# Outline Dimensions (inch )

.05	.05	.100	.020	<b>E</b> . <b>042</b> 1.07	.010	.23	.27	.30
grams	.100	.050	.125	P .600 15.24	.575	.26	.036	.020



### **Features**

- good return loss
- also available with plug-in (X65) and flat-pack (W38) leads

CASE STYLE: KK81 PRICE: \$6.95 ea. QTY (1-9)

# +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

## **Applications**

- amateur radio
- · impedance matching


### **Transformer Electrical Specifications**


Ω <b>RATIO</b> (Secondary/Primary)	FREQUENCY (MHz)	INSERTION LOSS*  3 dB 2 dB 1 dB			
		MHz	MHz	MHz	
36	0.03-20	0.03-20	0.05-10	0.1-5	

<sup>\*</sup>Insertion Loss is referenced to mid-band loss, 0.4 dB typ.

### **Typical Performance Data**

, ,			
FREQUENCY (MHz)	INSERTION LOSS (dB)	INPUT R. LOSS (dB)	
0.03	2.44	6.98	
0.05	1.60	9.75	
0.05	1.50	10.28	
0.10	0.89	15.22	
0.20	0.69	19.88	
0.27	0.67	20.32	
0.47	0.55	24.87	
2.17	0.38	16.92	
4.66	0.50	10.04	
20.00	2.58	1.81	





- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively "Standard Terms"): Purphasers of this part Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

  The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp