



AMP1082 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Class AB GaAs design
- Instantaneous wide Bandwidth
- Built-in protection circuits
- High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 18.0 GHz	
Power Output Psat	2 Watt Min	CW
Power Output P1dB GCP	1 Watt Min	CW
Small Signal Gain	33 dB Min	
Power Gain Flatness	4 dB p-p Max	
Input Return Loss	>10 dB Typ	
Harmonics	>20 dBc	At rated Pout
Noise Figure	6.0 dB Max	
Spurious	>60 dBc	Non Harmonics
Operating Voltage	15 VDC \pm 0.2 V	
Current Consumption	0.8 Amp Max	At rated Pout
Max Input Power	+8 dBm Max	Without damage
Load VSWR	5 : 1 Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +70 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	70 X 60 X 15 mm	Excluding Connectors
Weight	TBD	
RF Connectors In/Out	SMA female	Cover Flange
DC Power	Feed Thru	
Cooling	External Heatsink	Forced air required

PIN ASSIGNMENT

Pin	Function	Description
1	DC Voltage	+15VDC
2	GND	GND

OUTLINE DRAWING

