



## 50 Ohm SMA SP3T PIN Diode Switch Operating From 12 GHz to 18 GHz Up To +27 dBm

### TECHNICAL DATA SHEET

PE7124

#### 50 Ohm SMA SP3T PIN Diode Switch Operating From 12 GHz to 18 GHz Up To +27 dBm

##### Configuration

RF Connector	SMA Female
RF Connector Specification	MIL-C-39012
Control Connector	Solder Pin
Design	Absorptive, SP3T

##### Electrical Specifications

Frequency Range, GHz	12 to 18
Impedance, Ohms	50
Maximum Input Power, dBm	+27
Maximum Input VSWR	2:1
Maximum Insertion Loss, dB	3.2
Minimum Isolation, dB	65
Maximum Speed, ns	100
Power Supply 1, Volts	5
Power Supply 2, Volts	-15
Power Supply 2 Tolerance, Volts	3

##### Mechanical Specifications

###### Temperature

Operating Range, deg C	-55 to +85
Storage Range, deg C	-65 to +125

###### Size

Length, in [mm]	2.7 [68.58]
Width, in [mm]	0.5 [12.7]
Height, in [mm]	2.7 [68.58]

##### Compliance Certifications (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm SMA SP3T PIN Diode Switch Operating From 12 GHz to 18 GHz Up To +27 dBm PE7124](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



## 50 Ohm SMA SP3T PIN Diode Switch Operating From 12 GHz to 18 GHz Up To +27 dBm

### TECHNICAL DATA SHEET

PE7124

#### Plotted and Other Data

Notes:

Values at 25 °C, sea level

50 Ohm SMA SP3T PIN Diode Switch Operating From 12 GHz to 18 GHz Up To +27 dBm from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm SMA SP3T PIN Diode Switch Operating From 12 GHz to 18 GHz Up To +27 dBm PE7124](http://www.pasternack.com/50-ohm-sma-sp3t-pin-switch-12000-mhz-18000-mhz-0.5-watt-pe7124-p.aspx)

URL: <http://www.pasternack.com/50-ohm-sma-sp3t-pin-switch-12000-mhz-18000-mhz-0.5-watt-pe7124-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

