



Precision 2.92mm Male to 2.92mm Male Right Angle Adapter

TECHNICAL DATA SHEET

PE9645

Configuration

Connector 12.92mm MaleImpedance 150 OhmsConnector 22.92mm MaleImpedance 250 OhmsAdapter DesignPrecisionBody StyleRight Angle

Electrical Specifications

Frequency Range, GHz DC to 40 Maximum VSWR 1.35:1

Mechanical Specifications

Size

 Length, in [mm]
 0.62 [15.75]

 Width/Dia., in [mm]
 0.312 [7.92]

 Height, in [mm]
 0.67 [17.02]

Connector 1

2.92mm Male Inner Conductor Material and Plating Beryllium Copper, Gold Inner Conductor Plating Specification MIL-G-45204, Type II, Grade C, Class 1 Coupling Nut Material and Plating Passivated Stainless Steel Coupling Nut Plating Specification ASTM-A380 Hex Size, Inch 5/16 Torque, in-lbs [Nm] 8 [0.9] Body Material and Plating Passivated Stainless Steel **Body Plating Specification** ASTM-A380

Dielectric Type

Connector 2

Type 2.92mm Male Inner Conductor Material and Plating Beryllium Copper, Gold Inner Conductor Plating Specification MIL-G-45204, Type II, Grade C, Class 1 Coupling Nut Material and Plating Passivated Stainless Steel Coupling Nut Plating Specification ASTM-A380 Hex Size, Inch 5/16 Torque, in-lbs [Nm] 8 [0.9] Body Material and Plating Passivated Stainless Steel **Body Plating Specification** ASTM-A380 Dielectric Type Noryl

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision 2.92mm Male to 2.92mm Male Right Angle Adapter PE9645

Noryl

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





Precision 2.92mm Male to 2.92mm Male Right Angle Adapter

TECHNICAL DATA SHEET

PE9645

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes
REACH Compliant 06/18/2012

Plotted and Other Data

Notes: Values at 25 °C, sea level

Precision 2.92mm Male to 2.92mm Male Right Angle Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision 2.92mm Male to 2.92mm Male Right Angle Adapter PE9645

URL: http://www.pasternack.com/2.92mm-male-2.92mm-male-right-angle-adapter-pe9645-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9645 CAD Drawing
Precision 2.92mm Male to 2.92mm Male Right Angle Adapter

