



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS:

- FREQUENCY RANGE: 60-600 MHz
- POWER: 200 Watts CW
- FLATNESS: ±1.0dB Max.
- INSERTION LOSS: 0.30dB Max.
- VSWR: 1.20:1 Max.
- DIRECTIVITY: 20dB Min.
- COUPLING: 20dB

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE: N/A
			SHEET: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: HIGH POWER DUAL DIRECTIONAL COUPLER	
DRAWN: Paiboon Luexhamhan		PART NO.: HDL-23-20	
DATE: 12-20-2010		CAGE CODE: OD2L5	
APPROVED: T. Nguyen		DATE: 12-20-2010	
		SIZE: C	REV: N/A
		DWG NO.: 85152	
DO NOT SCALE THE DRAWING			