



Model: PD-N000-4S

Description:.....	4-Way Power Divider
Operating Frequency:.....	6-18 GHz
Insertion Loss:.....	1.3 dB Max
Isolation:.....	17 dB Min
VSWR:.....	Sum Port..... 1.60:1 Max
	Output Ports 1.60:1 Max
Amplitude Balance:.....	± 0.25 dB Max
Phase Balance:.....	± 4° Max
Power Handling (@ SUM Port):.....	Mismatch Loads 1W Avg/CW Max
	Matched Loads..... 10W Avg/CW Max
Connectors:.....	SMA (f), Removable
Impedance:.....	50 Ohms Nominal
Quality:.....	Best-Commercial-Grade

Environmental Ratings:

Temperature:.....	{Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity:.....	MIL-STD-202F, Method 103B Cond. B (96 hours at 95% R.H.)
Shock:.....	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:.....	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:.....	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:.....	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Outline

