

SPECIFICATION SHEET

JFW MODEL 57Z-2G & 75Z-2G

IMPEDANCE MATCHING PAD

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-2000 MHz

Impedance*
 57Z-2G: 50 Ohm male
 75 Ohm female
 75Z-2G: 75 Ohm male
 50 Ohm female

VSWR
 1.2:1 maximum DC-1000 MHz
 1.3:1 maximum 1000-2000 MHz

Attenuation Loss 5.7 dB ± 0.5 dB

RF Input Power 1 Watt average
 1000 Watts peak

RF Connector
 50 Ohm: SMA, BNC, TNC, N, N female
 panel mount or BNC female panel mount
 75 Ohm: BNC, TNC, N, F, or BNC female
 panel mount

Operating Temperature Range -20°C to +85°C

Physical Size See outline drawing:
 092-1069 (BNC F/BNC M)
 092-2278 (BNC F-PM/BNC M)
 092-2444 (BNC F/N M)
 092-3463 (BNC M/N F)
 092-2559 (N F/F M)
 092-164 (N F/N M)
 092-1903 (N M/BNC F)
 092-4282 (SMA F/F F)
 092-6746 (SMA M/F F)
 092-3487 (SMA M/N F)
 092-5202 (SMA F/BNC F)

* Standard impedances. Other configurations available.

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
2547	12/27/2000	D		12230	12/14/2005	G	CLK 12/14/2005
2552	01/05/2001	E		13399	09/21/2006	H	BAC 09/21/2006
9999	08/27/2003	F	SL 12/11/2003	19242	10/14/2010	I	TRS 10/14/2010