



AMP3037 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Class AB linear GaN design
- Instantaneous bandwidth
- Suitable for all modulations standards
- Built-in protection circuits
- High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	4.4 - 5.0 GHz	
Power Output	30 Watt Min	CW
Power Output @ P1dB	14 Watt Min	CW
Power Output @ COFDM	4 Watt Min	QAM 64, 1 carrier, EVM 2%
Power Gain	45 dB Min	
Small Signal Gain Flatness	4.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>40 dBc Typ	37 dBm/Tone, $\Delta = 1$ MHz
Harmonics	>30 dBc Typ	At rated Pout
Non Harmonics Spurious	>60 dBc Min	
Operating Voltage	28 VDC	
Current Consumption	7 Amp	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	$\infty : 1$	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	188 X 92 X 27 mm	Excluding Connectors
Weight	825 gr.	Max Weight
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	OPTION 101 - Forward power detect
2	VVA	N/C
3	CURRENT SENSOR	$I_p @ 50mV/100mA$ Typ
4	TEMP SENSOR	$V_T @ 10mV/^\circ C + 500mV$ Typ
5	SHUTDOWN	TTL
6, 7	VDD	28VDC
8, 9	GND	Ground

OUTLINE DRAWING - OPTION 101

