

SPECIFICATION SHEET
JFW MODEL 50FH-XXX-80-3
FIXED ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

| | |
|-----------------------------|---|
| Frequency Range | DC-3000 MHz |
| Impedance | 50 Ohms nominal |
| Attenuation Values | 1 thru 50 dB in any 1 dB increment |
| VSWR | For 1-14 dB: 1.4:1 maximum For 15-50 dB: 1.3:1 maximum |
| Attenuation Accuracy | ± 0.5 dB maximum |
| RF Input Power | 80 Watts average @ +25°C Derate to 40 Watts @ +85°C |
| Peak Power | 1000 Watts (1 microsecond pulse) |
| RF Connector | BNC, N, SMA, TNC, 4.1-9.5, 4.3-10.0 or 7/16 |
| Operating Temperature Range | -55°C to +100°C |
| Physical Size | See outline drawing 092-6447 |

| ECR/ECN # | DATE | REV | APPR / DATE | ECR/ECN # | DATE | REV | APPR / DATE |
|-----------|------------|-----|----------------|-----------|------|-----|-------------|
| | 10/22/2013 | | TRS 10/22/2013 | | | | |
| 26007 | 12/14/2015 | A | CLK 12/14/2015 | | | | |