



LABEL EXAMPLE ONLY.
SEE TABLE FOR TYPE No.

TYPE NUMBER	FREQUENCY (GHz.)	TYPICAL			-10°C to +65°C.		
		INSERTION LOSS (dB Max.)	RETURN LOSS (dB Min.)	ISOLATION (dB Min.)	INSERTION LOSS (dB Max.)	RETURN LOSS (dB Min.)	ISOLATION (dB Min.)
SG 10523	2.8 - 3.2	0.3	23	23	0.4	20	20
SG 10524	3.2 - 3.6	0.3	23	23	0.4	20	20
SG 10525	3.6 - 4.0	0.3	23	23	0.4	20	20
CG 10540	4.0 - 8.0	0.4	20	20	0.5	18	18
CG 10541	4.0 - 4.8	0.3	23	23	0.4	20	20
CG 10542	4.8 - 5.6	0.3	23	23	0.4	20	20

Q.A.
DATE
PROD.REL.
DATE
ENG.APP.
DATE

B	01.04.10	DRN VARIOUS
ISSUE	DATE	MOD NUMBER

NOTES : THIS UNIT IS RoHS COMPLIANT by DESIGN.
LIGHTLY REMOVE ALL BURRS AND SHARP EDGES U.O.S.

THIS DRAWING IS MESL Microwave Ltd. PROPERTY.
IT MAY NOT BE COPIED OR EXHIBITED WITHOUT WRITTEN PERMISSION.

A 3

MECH.ENG. DATE	ORIGINAL SCALE 2:1 DO NOT SCALE PRINT	MATERIAL	SPECIFICATION	GENERAL TOLERANCE U.O.S. (ISO2768-MH) 0 - 6.0 : ±0.05 120.0 - 400.0 : ±0.2 6.0 - 30.0 : ±0.1 400.0 - 1000.0 : ±0.3 30.0 - 120.0 : ±0.15 1000.0 - 2000.0 : ±0.5 Angular Dim : ±0.5° Symmetry ±0.05	RESPONSIBLE AUTHORITY	SECURITY CLASSIFICATION
DRAWN AB. DATE 14/12/09	MASS (kg): N/A DENSITY (g/cm³): N/A	FINISH BODY / LID : SurTec 650 ChromiAL PLATES : BRIGHT NICKEL.	SPECIFICATION	FINISH TO BE 1.6/√ U.O.S. DIMENSION IN mm	TITLE 2.8-8GHz COAXIAL CIRCULATOR OUTLINE TYPE No SEE TABLE	CONTRACTORS DRAWING NUMBER 10523 to 10542-000-OL SERVICE DRAWING NUMBER
					SHEET No. 1 OFF 1	