

SPECIFICATION SHEET

JFW MODEL 50T-376

TERMINATION

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-4000 MHz

Impedance 50 Ohms nominal

VSWR 1.10:1 maximum
1.04:1 typical

RF Input Power 2 Watts average

Peak Power 1000 Watts

RF Connector SMA, N, TNC or BNC
(male or female)

Operating Temperature Range -20°C to +85°C

Physical Size See outline drawings:

092-4072 (50T-376 SMA F)
092-4269 (50T-376 SMA M)

092-7065 (50T-376 N F)
092-4208 (50T-376 N M)

092-7064 (50T-376 TNC F)
092-4444 (50T-376 TNC M)

092-7066 (50T-376 BNC F)
092-6043 (50T-376 BNC M)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/22/2002		TRS 10/22/2002	4470	02/11/2004	C	CLV 02/11/2004
4324	08/04/2003	A	CLV 08/04/2003	4542	03/30/2004	D	CLV 03/30/2004
4442	01/27/2004	B	SL 01/27/2004	20493	08/23/2011	E	TRS 08/24/2011