



3 dB Fixed Attenuator, TNC Male To TNC Female Brass
Nickel Body Rated To 2 Watts Up To 12.4 GHz

TECHNICAL DATA SHEET

PE7051-3

3 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 2 Watts Up To 12.4 GHz

Configuration

Design	Fixed, Bidirectional Attenuator
Connector 1	TNC Male
Connector 2	TNC Female
Body Material and Plating	Brass, Nickel

Electrical Specifications

Frequency Range, GHz	DC to 12.4
Impedance, Ohms	50
Attenuation Value, dB	3
Maximum Input Power, Watts	2
Maximum VSWR	1.25:1

Frequency 1

Range, GHz	DC to 12.4
VSWR	1.25:1
Attenuation Accuracy, dB	± 0.3

Mechanical Specifications

Size

Length, in [mm]	1.35 [34.29]
Width, in [mm]	0.59 [14.99]

Connector 1

Type	TNC Male
Connector Specification	MIL-STD-348
Contact Material and Plating	Beryllium Copper, Gold
Coupling Nut Material and Plating	Brass, Nickel
Body Material and Plating	Brass, Nickel

Connector 2

Type	TNC Female
Connector Specification	MIL-STD-348
Contact Material and Plating	Beryllium Copper, Gold
Body Material and Plating	Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 2 Watts Up To 12.4 GHz PE7051-3](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



3 dB Fixed Attenuator, TNC Male To TNC Female Brass
Nickel Body Rated To 2 Watts Up To 12.4 GHz

TECHNICAL DATA SHEET

PE7051-3

Plotted and Other Data

Notes:

Values at 25 °C, sea level

3 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 2 Watts Up To 12.4 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 2 Watts Up To 12.4 GHz PE7051-3](http://www.pasternack.com/3db-fixed-tnc-male-tnc-female-2-watts-attenuator-pe7051-3-p.aspx)


URL: <http://www.pasternack.com/3db-fixed-tnc-male-tnc-female-2-watts-attenuator-pe7051-3-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE7051-3 CAD Drawing

3 dB Fixed Attenuator, TNC Male To TNC Female Brass
Nickel Body Rated To 2 Watts Up To 12.4 GHz

P/N	ATTEN.	FIGURE
PE7051-1	1 dB	1
PE7051-2	2 dB	1
PE7051-3	3 dB	1
PE7051-6	6 dB	1
PE7051-10	10 dB	1
PE7051-20	20 dB	1
PE7051-30	30 dB	1
PE7051-40	40 dB	1



TNC FEMALE

FIGURE 1

TNC MALE

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE

PE7051

FSCM NO. 53919

CAD FILE 030613

SCALE N/A

SIZE A

XXX

PASTERNACK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com