

ADS-A8PC8	SMA Jack To 3.5 Jack	50Ω												
<p>Typical VSWR</p> <table border="1" style="margin: auto; border-collapse: collapse;"> <thead> <tr> <th>Part Number</th> <th>1~6Ghz</th> <th>7~12Ghz</th> <th>13~18Ghz</th> <th>19~27Ghz</th> <th>28~33Ghz</th> </tr> </thead> <tbody> <tr> <td>ADS-A8PC8</td> <td>1.05</td> <td>1.1</td> <td>1.15</td> <td>1.2</td> <td>1.25</td> </tr> </tbody> </table>			Part Number	1~6Ghz	7~12Ghz	13~18Ghz	19~27Ghz	28~33Ghz	ADS-A8PC8	1.05	1.1	1.15	1.2	1.25
Part Number	1~6Ghz	7~12Ghz	13~18Ghz	19~27Ghz	28~33Ghz									
ADS-A8PC8	1.05	1.1	1.15	1.2	1.25									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Parts</th> <th style="width: 20%;">Material</th> <th style="width: 65%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 20 Over Nickel 50 Over Copper 50</td> </tr> <tr> <td>Insulator</td> <td>P.P.O</td> <td></td> </tr> <tr> <td>Body</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Contact Pin	Beryllium Copper	Gold 20 Over Nickel 50 Over Copper 50	Insulator	P.P.O		Body	Stainless Steel	Passivated
Parts	Material	Plating (Micro-inch)												
Contact Pin	Beryllium Copper	Gold 20 Over Nickel 50 Over Copper 50												
Insulator	P.P.O													
Body	Stainless Steel	Passivated												
<p>Weight:</p>														

This part number complies with RoHS.

Notice: JYBAO reserves the right to make modifications deemed appropriate.