

## B R O A D W A V E T E C H N O L O G I E S I N C .

## MODEL 354 - 095 - XXX\*

## FIXED ATTENUATOR

<b>Frequency Range:</b>	<b>DC - 2000 MHz</b>
<b>Impedance:</b>	<b>50 Ohms nominal</b>
<b>Attenuation Value:</b>	<b>1 - 40 dB available</b>
<b>Attenuation Accuracy:</b>	<b>± 0.5 dB maximum ( 1 - 20 dB ) ± 0.75 dB maximum ( 21 - 40 dB )</b>
<b>VSWR:</b>	<b>DC - 1000 MHz    1.3:1 maximum 1000 - 2000 MHz    1.4:1 maximum</b>
<b>Power Input:</b>	<b>1 Watt average</b>
<b>RF Connectors:</b>	<b>BNC Male / Female</b>
<b>Operating Temperature Range:</b>	<b>- 55°C to +100°C</b>
<b>Outline Drawing:</b>	<b>MED – 0107 ( 1 - 20 dB ) MED – 0225 ( 21 - 40 dB )</b>

\*Insert desired attenuation value  
( example: 3 dB = 003 )

<b>ECF #</b>	<b>Date</b>	<b>Rev.</b>
Issue	03/06/03	0
0606	04/08/08	A
0613	04/21/08	B
0694	10/6/08	C
0931	12/10/09	D

**Approved By:** \_\_\_\_\_