

SMA Female to MCX Jack Adapter



PE9470

TECHNICAL DATA SHEET

SMA Female to MCX Jack Adapter	
Configuration Connector 1 Impedance 1 Connector 2 Impedance 2 Adapter Design Body Style	SMA Female 50 Ohms MCX Jack 50 Ohms Standard Straight
Size Length, in [mm] Width/Dia., in [mm]	0.633 [16.08] 0.25 [6.35]
Connector 1 Type Inner Conductor Material and Plating Body Material and Plating Dielectric Type	SMA Female Gold Brass, Nickel PTFE
Connector 2 Type Inner Conductor Material and Plating Body Material and Plating Dielectric Type	MCX Jack Gold Brass, Nickel PTFE
Compliance Certifications (visit www.Pasternack.com for cu RoHS Compliant	urrent document) Yes
Plotted and Other Data Notes:	Values at 25 °C, sea level
URL: http://www.pasternack.com/sma-female-mcx-jack-straight-adapter-pe9470-p.aspx	

SMA Female to MCX Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9470 CAD Drawing

SMA Female to MCX Jack Adapter

