

Specifications


Parameter	Unit	Min	Typical	Max
Center Frequency (F0)	MHz		114.765	
Bandwidth (B)	MHz		12.5	
-3 dB Bandwidth (B3)	MHz	14.1	14.3	
-40 db Bandwidth (B40)	MHz		17.1	17.2
Delay (T0)	μsec	0.94	0.945	0.95
Insertion Loss (IL)	dB		27.4	28
Amplitude Ripple	dB p-p		0.4	0.5
Phase Ripple	deg p-p		3.4	5
Rejection	dB	46	49	
Spurious for t-T0 >.9T0	dB		-37	-36
Substrate Material		128YX-LN		

Notes:

- Center Frequency (F0) and Bandwidth (B) are defined, not measured.
- Insertion Loss is the minimum loss for $|f-F0| < .5B$
- Ripple spec applies to the $|f-F0| < .4B$, and is doubled for $.4B < |f-F0| < .5B$
- Rejection spec applies to $(B/2) < |f-F0| < F0/2$
- Specifications are at 22C only. Unit will operate undamaged from -54C to 125C with shifts $dF0 = -x \cdot F0$, $dT0 = x \cdot T0$, where $x = 75E-6 \cdot (\text{temperature} - 22C)$

Typical Performance


Frequency Response
(Best Fit Linear Phase Removed)



10 dB/div, 1 dB/div, 10 deg/div, 5.000 MHz/div

Impulse Response



FFT(Frequency Response * Cos(0.5*PI*MIN(1,MAX(0,|f-F0|^2.0/12.5-1.0)))^2)



10 dB/div, 0.400 us/div

Package Outline

Matching



Matched S-parameters available at www.phonon.com