


REVISIONS

REV.	DESCRIPTION	ECO	DATE	APPROVED
1	INITIAL RELEASE	-	04/10/13	P.T

THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY. DO NOT REVISE MANUALLY.



Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	1805		1880
Insertion Loss (dB)		< .20	.30
Isolation (dB)	22	> 25	
Return Loss (dB)	22	> 25	
FWD IMD: 2T at 37W per T 5MHz Spacing (dBc)		75	

Power & Temperature Ratings

Parameter	Maximum
Forward PWR Peak/AVG	1000/200 Watts
Reverse Power CW	200 Watts
Operating Temperature	-40 to +85° C
Storage Temperature	-40 to +95° C

Notes:

1. Typical Values Represent Mid-Band Performance @ +23 °C.
2. Tab dims: .64[.025]Width x 3.0[.12]Length x .20[.008]Thick

CW CIRCULATOR MODEL: RFCR2502

<p>UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]:</p> <p>TOLERANCES ARE:</p> <table border="1"> <tr> <td>1 PLACE DECIMAL ±.2 [±.01]</td> <td>ANGULAR: ±1.0°</td> </tr> <tr> <td>2 PLACE DECIMAL ±.10 [±.004]</td> <td>SURFACE ROUGHNESS 16/</td> </tr> </table> <p>REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING &amp; TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5</p> <p>PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RF CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."</p>	1 PLACE DECIMAL ±.2 [±.01]	ANGULAR: ±1.0°	2 PLACE DECIMAL ±.10 [±.004]	SURFACE ROUGHNESS 16/	<p>THIRD ANGLE PROJECTION</p>	<p><b>RFCI</b></p>									
	1 PLACE DECIMAL ±.2 [±.01]	ANGULAR: ±1.0°													
2 PLACE DECIMAL ±.10 [±.004]	SURFACE ROUGHNESS 16/														
<p>APPROVALS</p> <table border="1"> <tr> <td>DRAWN BY: HV</td> <td>DATE: 04/13/13</td> </tr> <tr> <td>CHECKED BY: P.T</td> <td>DATE: 04/14/13</td> </tr> <tr> <td>DESIGN BY: P.T</td> <td>DATE: 01/10/13</td> </tr> <tr> <td>ENGINEER BY: P.T</td> <td>DATE: 01/10/13</td> </tr> <tr> <td>MFG. ENGR. L.T</td> <td>DATE: 02/10/13</td> </tr> <tr> <td>Q.A.</td> <td></td> </tr> <tr> <td>PROG. MGMT/MKT</td> <td></td> </tr> </table>	DRAWN BY: HV	DATE: 04/13/13	CHECKED BY: P.T	DATE: 04/14/13	DESIGN BY: P.T	DATE: 01/10/13	ENGINEER BY: P.T	DATE: 01/10/13	MFG. ENGR. L.T	DATE: 02/10/13	Q.A.		PROG. MGMT/MKT		<p>TITLE</p> <p><b>OUTLINE/SPECS</b></p>
DRAWN BY: HV	DATE: 04/13/13														
CHECKED BY: P.T	DATE: 04/14/13														
DESIGN BY: P.T	DATE: 01/10/13														
ENGINEER BY: P.T	DATE: 01/10/13														
MFG. ENGR. L.T	DATE: 02/10/13														
Q.A.															
PROG. MGMT/MKT															
<p>DO NOT SCALE DRAWING</p>	<p>SCALE: FULL</p>	<p>SIZE: A</p> <p>CAGE NO.</p> <p>DWG NO. <b>CR2502-OS</b></p> <p>REV. <b>1</b></p>													
		<p>SHEET 1 OF 1</p>													