



50 dB Fixed Attenuator, TNC Female To 7/16 DIN Female Rated To 25 Watts Up To 6 GHz

TECHNICAL DATA SHEET

PE7376-50

50 dB Fixed Attenuator, TNC Female To 7/16 DIN Female Rated To 25 Watts Up To 6 GHz

Configuration

Design Fixed, Bidirectional Attenuator

Connector 1 **TNC Female** Connector 2 7/16 DIN Female

Body Material and Plating Aluminum Heatsink, Black Anodized

Electrical Specifications

Frequency Range, GHz DC to 6 Impedance, Ohms 50 Attenuation Value, dB 50 to 50 Maximum Input Power, Watts 25 1.3:1

Maximum VSWR

Frequency 1 Range, GHz DC to 6 Insertion Loss, dB 50 **VSWR** 1.3:1 Attenuation Accuracy, dB 1.25 Maximum Input Power, Watts 25

Frequency 2

Mechanical Specifications

Temperature

Operating Range, deg C -55 to +125

Size

Length, in [mm] 4.5 [114.3] Width, in [mm] 2.41 [61.21] Weight, lbs [g] 0.8 [362.87]

Connector 1

Type **TNC Female** Contact Material and Plating Brass, Gold Contact Plating Specification Gold Hex Size, In. 11/16

Body Material and Plating Stainless Steel, Passivated

Body Plating Specification Passivated

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 dB Fixed Attenuator, TNC Female To 7/16 DIN Female Rated To 25 Watts Up To 6 GHz PE7376-50

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001: 2008 Registered



50 dB Fixed Attenuator, TNC Female To 7/16 DIN Female Rated To 25 Watts Up To 6 GHz



TECHNICAL DATA SHEET

PE7376-50

Connector 2

Type 7/16 DIN Female
Contact Material and Plating Brass, Silver
Outer Conductor Material and Plating Brass, Silver
Hex Size, In. 11/16
Body Material and Plating Brass, Silver

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/50db-fixed-tnc-female-7-16-female-25-watts-attenuator-pe7376-50-p.aspx

50 dB Fixed Attenuator, TNC Female To 7/16 DIN Female Rated To 25 Watts Up To 6 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE7376-50 CAD Drawing

50 dB Fixed Attenuator, TNC Female To 7/16 DIN Female Rated To 25 Watts Up To 6 GHz

