



10 dB Fixed Attenuator, TNC Male To TNC Female  
Brass Nickel Body Rated To 1 Watt Up To 2 GHz

TECHNICAL DATA SHEET

PE7003-10

**10 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 1 Watt Up To 2 GHz**

**Configuration**

Design	Fixed, Bidirectional Attenuator
Connector 1	TNC Male
Connector 2	TNC Female
Body Material and Plating	Brass, Nickel

**Electrical Specifications**

Frequency Range, GHz	DC to 2
Impedance, Ohms	50
Attenuation Value, dB	10
Maximum Input Power, Watts	1
Maximum VSWR	1.2:1

**Frequency 1**

Range, GHz	DC to 2
Attenuation Accuracy, dB	± 0.5

**Mechanical Specifications**

**Temperature**

Operating Range, deg C	-65 to +165
------------------------	-------------

**Size**

Length, in [mm]	1.84 [46.74]
Width, in [mm]	0.59 [14.99]

**Connector 1**

Type	TNC Male
Contact Material and Plating	Brass, Gold
Coupling Nut Material and Plating	Brass, Nickel
Body Material and Plating	Brass, Nickel

**Connector 2**

Type	TNC Female
Contact Material and Plating	Beryllium Copper, Gold
Body Material and Plating	Brass, Nickel

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 1 Watt Up To 2 GHz PE7003-10](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



10 dB Fixed Attenuator, TNC Male To TNC Female  
Brass Nickel Body Rated To 1 Watt Up To 2 GHz

TECHNICAL DATA SHEET

PE7003-10

**Plotted and Other Data**

Notes:

Values at 25 °C, sea level

10 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 1 Watt Up To 2 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, TNC Male To TNC Female Brass Nickel Body Rated To 1 Watt Up To 2 GHz PE7003-10](http://www.pasternack.com/10db-fixed-tnc-female-tnc-male-1-watt-attenuator-pe7003-10-p.aspx)

URL: <http://www.pasternack.com/10db-fixed-tnc-female-tnc-male-1-watt-attenuator-pe7003-10-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

# PE7003-10 CAD Drawing

10 dB Fixed Attenuator, TNC Male To TNC Female Brass  
Nickel Body Rated To 1 Watt Up To 2 GHz

P/N	ATTEN.	FIGURE
PE7003-1	1 dB	2
PE7003-2	2 dB	1
PE7003-3	3 dB	1
PE7003-6	6 dB	1
PE7003-10	10 dB	2
PE7003-20	20 dB	2
PE7003-30	30 dB	2
PE7003-40	40 dB	2





FIGURE 1



TNC MALE

FIGURE 2

TNC FEMALE



Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623  
Phone: (949) 261-1920 | Fax: (949) 261-7451  
Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)

DWG TITLE

**PE7003**

FSCM NO. 53919

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE 022113

SCALE N/A

SIZE A

2231