



D-Sub Plug to D-Sub Plug Adapter

TECHNICAL DATA SHEET

PE9688

D-Sub Plug to D-Sub Plug Adapter

Configuration

Connector 1D-Sub PlugImpedance 150 OhmsConnector 2D-Sub PlugImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Size

Length, in [mm] 1.175 [29.85] Width/Dia., in [mm] 0.218 [5.54]

Connector 1

Type D-Sub Plug Inner Conductor Material and Plating Gold Body Material and Plating Brass, Gold Dielectric Type PTFE

Connector 2

Type D-Sub Plug Inner Conductor Material and Plating Gold Body Material and Plating Brass, Gold Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

D-Sub Plug to D-Sub Plug Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: D-Sub Plug to D-Sub Plug Adapter PE9688

URL: http://www.pasternack.com/d-sub-plug-d-sub-plug-straight-adapter-pe9688-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9688 CAD Drawing

D-Sub Plug to D-Sub Plug Adapter

