



10 dB Fixed Attenuator, N Male To TNC Female
Rated To 25 Watts Up To 18 GHz

TECHNICAL DATA SHEET

PE7368-10

10 dB Fixed Attenuator, N Male To TNC Female Rated To 25 Watts Up To 18 GHz

Configuration

Design	Fixed, Bidirectional Attenuator
Connector 1	N Male
Connector 2	TNC Female
Body Material and Plating	Aluminum Heatsink, Black Anodized

Electrical Specifications

Frequency Range, GHz	DC to 18
Impedance, Ohms	50
Attenuation Value, dB	10 to 10
Maximum Input Power, Watts	25
Maximum VSWR	1.45:1

Frequency 1

Range, GHz	DC to 6
Insertion Loss, dB	10
VSWR	1.3:1
Attenuation Accuracy, dB	0.5
Maximum Input Power, Watts	25

Frequency 2

Range, GHz	6 to 7.5
VSWR	1.45:1
Attenuation Accuracy, dB	0.75

Frequency 3

Range, GHz	7.5 to 18
VSWR	1.6:1
Attenuation Accuracy, dB	1.25

Mechanical Specifications

Temperature

Operating Range, deg C	-55 to +125
------------------------	-------------

Size

Length, in [mm]	4.5 [114.3]
Width, in [mm]	2.41 [61.21]
Weight, lbs [g]	0.8 [362.87]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, N Male To TNC Female Rated To 25 Watts Up To 18 GHz PE7368-10](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



10 dB Fixed Attenuator, N Male To TNC Female
Rated To 25 Watts Up To 18 GHz

TECHNICAL DATA SHEET

PE7368-10

Connector 1

Type	N Male
Contact Material and Plating	Brass, Gold
Contact Plating Specification	Silver
Hex Size, In.	11/16
Body Material and Plating	Stainless Steel, Passivated
Body Plating Specification	Passivated

Connector 2

Type	TNC Female
Contact Material and Plating	Beryllium Copper, Gold
Outer Conductor Material and Plating	Stainless Steel, Passivated
Hex Size, In.	11/16
Body Material and Plating	Stainless Steel, Passivated

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------

URL: <http://www.pasternack.com/10db-fixed-n-male-tnc-female-25-watts-attenuator-pe7368-10-p.aspx>

10 dB Fixed Attenuator, N Male To TNC Female Rated To 25 Watts Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE7368-10 CAD Drawing

10 dB Fixed Attenuator, N Male To TNC Female Rated To 25 Watts Up To 18 GHz

xx	Input Connector	Output Connector	Part Number Configuration
55	SMA Male	7/16 Female	
56	SMA Male	N Female	
57	SMA Male	SMA Female	
58	SMA Male	TNC Female	
59	SMA Female	7/16 Female	
60	SMA Female	7/16 Male	
61	SMA Female	N Female	
62	SMA Female	N Male	
63	SMA Female	SMA Female	
64	SMA Female	TNC Female	
65	SMA Female	TNC Male	
66	N Male	7/16 Female	
67	N Male	N Female	
68	N Male	TNC Female	
69	N Female	7/16 Female	
70	N Female	7/16 Male	
71	N Female	N Female	
72	N Female	TNC Female	
73	N Female	TNC Male	
74	TNC Male	TNC Female	
75	TNC Male	SMA Male	
76	TNC Female	7/16 Female	
77	TNC Female	7/16 Male	
78	TNC Female	TNC Female	
79	7/16 Male	7/16 Female	
80	7/16 Female	7/16 Female	
-yy			Indicates Attenuation Level

Connector Type	DIM "A" (REF.)
SMA Male	0.68
SMA Female	0.54
TNC Male	0.98
TNC Female	0.94
N Female	0.95
N Male	0.98
7/16 Male	1.12
7/16 Female	1.16



NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE73xx-yy

PE PASTERNAK
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919
 CAD FILE 102512
 SCALE N/A
 SIZE A
 2233