

# 30 dB Fixed Attenuator, N Male To 7/16 DIN Female Rated To 25 Watts Up To 7.5 GHz



# **TECHNICAL DATA SHEET**

PE7366-30

## 30 dB Fixed Attenuator, N Male To 7/16 DIN Female Rated To 25 Watts Up To 7.5 GHz

Configuration
---------------

Design Fixed, Bidirectional Attenuator

Connector 1 N Male

Connector 2 7/16 DIN Female

Body Material and Plating Aluminum Heatsink, Black Anodized

### **Electrical Specifications**

Frequency Range, GHz

Impedance, Ohms

Attenuation Value, dB

Maximum Input Power, Watts

Maximum VSWR

DC to 7.5

50

30 to 30

1.45:1

#### Frequency 1

Range, GHz DC to 6
Insertion Loss, dB 30
VSWR 1.3:1
Attenuation Accuracy, dB 0.5
Maximum Input Power, Watts 25

## Frequency 2

Range, GHz 6 to 7.5 VSWR 1.45:1 Attenuation Accuracy, dB 0.75

#### **Mechanical Specifications**

Temperature

Operating Range, deg C -55 to +125

Size

 Length, in [mm]
 4.5 [114.3]

 Width, in [mm]
 2.41 [61.21]

 Weight, lbs [g]
 0.8 [362.87]

# Connector 1

Type N Male
Contact Material and Plating Brass, Gold
Contact Plating Specification Gold
Hex Size, In. 11/16

Body Material and Plating Stainless Steel, Passivated

Body Plating Specification Passivated

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 30 dB Fixed Attenuator, N Male To 7/16 DIN Female Rated To 25 Watts Up To 7.5 GHz PE7366-30

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered



# 30 dB Fixed Attenuator, N Male To 7/16 DIN Female Rated To 25 Watts Up To 7.5 GHz



# **TECHNICAL DATA SHEET**

PE7366-30

Connector 2

Type 7/16 DIN Female Brass, Silver Contact Material and Plating Outer Conductor Material and Plating Brass, Silver Hex Size, In. 11/16 Body Material and Plating Brass, Silver

Compliance Certifications (visit www.Pasternack.com for current document)

**RoHS Compliant** 

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/30db-fixed-n-male-7-16-female-25-watts-attenuator-pe7366-30-p.aspx

30 dB Fixed Attenuator, N Male To 7/16 DIN Female Rated To 25 Watts Up To 7.5 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# PE7366-30 CAD Drawing

30 dB Fixed Attenuator, N Male To 7/16 DIN Female Rated To 25 Watts Up To 7.5 GHz

