


Features

- 3 dBm Output Level at 1810 MHz
- Channel Step Size : 25 kHz
- 2nd Harmonic : < -20 dBc
- Spurious Level : < -60 dBc
- Lock Time : < 10 ms
- 40 mA Current Consumption

Description

The plerow™ PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



Specifications

Parameter	Unit	Min.	Typical	Max.
Frequency Range	MHz	1780	1810	1840
Output Power	dBm	1	3	5
Supply Voltage	V	4.75	5	5.25
Current Consumption	mA			40
Channel Step Size	kHz		25	
2 nd Harmonics	dBc			-20
Spurious Level	dBc			-60
Lock Time	ms		5	10
Reference Frequency(internal)	MHz		13	
Reference Input Level	dBm			
Phase Noise (C / N)				
@ 1 kHz			-70	-60
@ 10 kHz	dBc/Hz		-100	-90
@ 100 kHz			-120	-110
Output Impedance	Ω		50	
Operating Temp. Range	°C	-40	25	85
Package Type & Size	mm	SMT, 19.0W×19.0L×5.8H		

1) Measurement conditions are as follows: T = 25°C, V_{CC} = 5 V, Freq. = 1810 MHz, 50 ohm system.

2) Frequency stability of internal ref. TCXO is +/-2.5 ppm(max.) over the operating temperature range.

More Information

Website: www.asb.co.kr
E-mail: sales@asb.co.kr


Tel: (82) 42-528-7220
Fax: (82) 42-528-7222

ASB, Inc., 4th Fl. Venture Town
Bldg, KT HRDC, 367-17 Goi-
jeong-Dong, Seo-Gu, Daejeon,
302-716, Korea

Outline Drawing

APL0000-T Type

Type	Dimension
PLL IC + VCO + TCXO	19 x 19 x 5.8



Pin Out for PLL			
Pin No.	Application	Pin No.	Application
1	CLOCK	9	VCC (VCO)
2	DATA	13	RF OUT
3	ENABLE	15	VCC (PLL)
4	GROUND	16	LOCK DETECT
All other Pins are Grounded / Internal TCXO			

