



Medium Power 50 Watts RF Load Up To 4 GHz With 7/16 DIN Male Input Square Body Black Anodized Aluminum Heatsink

TECHNICAL DATA SHEET

PE6169

Configuration

Connector 7/16 DIN Male

Heat Sink Black Anodized Aluminum Heatsink

Body Style Straight

Electrical Specifications

Frequency Range, GHz

Impedance, Ohms

Maximum VSWR

Maximum Input Power, Watts

Peak Power, KWatts

DC to 4

1.25:1

50

Feak Power, KWatts

Frequency 1

Frequency, GHz DC to 2 VSWR 1.15:1

Frequency 2

Frequency, GHz 2 to 4 VSWR 2 to 4

Mechanical Specifications

Size

 Length, in [mm]
 5.15 [130.81]

 Width/Dia., in [mm]
 2.765 [70.23]

 Height, in [mm]
 3.5 [88.9]

Connector

Type 7/16 DIN Male
Inner Conductor Material and Plating Gold
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Medium Power 50 Watts RF Load Up To 4 GHz With 7/16 DIN Male Input Square Body Black Anodized Aluminum Heatsink PE6169

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





Medium Power 50 Watts RF Load Up To 4 GHz With 7/16 DIN Male Input Square Body Black Anodized Aluminum Heatsink

TECHNICAL DATA SHEET

PE6169

Plotted and Other Data

Notes:

Values at 25 °C, sea level

Medium Power 50 Watts RF Load Up To 4 GHz With 7/16 DIN Male Input Square Body Black Anodized Aluminum Heatsink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Medium Power 50 Watts RF Load Up To 4 GHz With 7/16 DIN Male Input Square Body Black Anodized Aluminum Heatsink PE6169

URL: http://www.pasternack.com/50-watts-7-16-male-rf-load-up-to-4-ghz-pe6169-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



ISO 9001: 2008 Registered

PE6169 CAD Drawing

Medium Power 50 Watts RF Load Up To 4 GHz With 7/16 DIN Male Input Square Body Black Anodized Aluminum Heatsink

