

5

4

3


2

1

**PRODUCTION
RELEASE**

REVISIONS

LTR	DESCRIPTION	DATE	APPROVED
B	ADDED STORAGE TEMP	3/29/10	T. KUHN



**M07
NOTES:**

- MATERIAL:**
HOUSING: STAINLESS STEEL IAW ASTM-A484 & ASTM-A582, ALLOY 303,
COND A
CONTACT: BERYLLIUM COPPER
DIELECTRIC - HIGH TEMPERATURE PLASTIC BEAD
- FINISH:**
HOUSING - PASSIVATED STAINLESS STEEL
CONDUCTOR - GOLD PLATED IAW MIL-PRF-39012
- ELECTRICALS:**
VSWR (MAX) DC-50 GHz 1.10+ f_{GHz} (.01) MAX.

POWER (AVG. MAX.) @25°C SEE TABLE
DERATES LINEARLY TO 10% @ +100°C
OPERATING/STORAGE TEMPERATURE RANGE °C-55 to +100

ORDERING INFORMATION

8501-700X-02	POWER LEVEL
X = 0	0.5 WATT
X = 1	1 WATT

8501-700X-02 NO CHAIN
8501-700X-02-C 2' CHAIN ADDED

DRAWING PRACTICES PER ANSI-Y-14.5 MIL-STD-100 & 1000	UNLESS OTHERWISE SPECIFIED TOLERANCES IN:
DIMENSIONS ARE IN INCHES AND APPLY BEFORE/AFTER PROCESSING	DECIMALS INCH MM
SURFACE ROUGHNESS 63 ✓	.X" .03" [.76]
FINISH SEE NOTES	.XX" .010" [.25]
MATERIAL SEE NOTES	.XXX" .005" [.127]
	.XXXX" .0005" [.013]
	ANGLES ±0°30'
	REMOVE ALL BURRS/SHARP W/ BREAK / R OF .003" TO .0005" UNLESS OTHERWISE NOTED DIAS CONCENTRIC <.003 T.I.R.

DRAWN T. KUHN	DATE 1/26/09
CHECKED	DATE
ENG.	DATE
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF XMA CORP. OR OMNI SPECTRA AND SHALL NOT BE REPRODUCED, COPIED NOR USED - IN WHOLE OR IN PART - AS A BASIS FOR THE MANUFACTURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS WRITTEN PERMISSION OF XMA CORP.	

XMA Omni Spectra™
150 Dow Street, Manchester, NH 03101 P:603-222-2256 F:603-222-2259

TITLE
TERMINATION, 2.4mm, MALE,
DC-50GHz

SIZE B	CAGE CODE 3HT76	DRAWING NUMBER 8501-700X-02 (OPT "C")
SCALE 6:1	PLATED AREA XXX	SHEET 1 OF 1

5

4

3

2

1

BCSI