

SPECIFICATION SHEET

JFW MODEL 50BR-105

BENCH TOP ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-8 GHz
Impedance	50 Ohms nominal
Attenuation Range	0-69 dB in 1 dB steps
VSWR	1.6:1 maximum DC-4 GHz 1.9:1 maximum 4-8 GHz
Attenuation Accuracy	± 0.5 dB (1 dB steps) ± 1.0 dB or 3% (10 dB steps)
Insertion Loss	1.8 dB maximum
RF Input Power	2 Watts average @ 25°C Derate to 1 Watt average @ 50°C 200 Watts peak (1 microsecond pulse)
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	(1 dB steps) 36 degrees with no stop between minimum and maximum settings (10 dB steps) 36 degrees with stop between minimum and maximum settings
RF Connector	SMA female
Operating Temperature Range	0°C to +50°C
Physical Size	See outline drawing 092-5899

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/16/2008		TRS 09/16/2008				
23479	11/26/2013	A	TRS 11/27/2013				