

ADS-K8PL3	Stainless K Jack To SMP Plug Limited Detent	50Ω															
<p>The drawing shows a side view and an end view of the connector. The side view includes the following dimensions: a threaded section of 1/4-36UNS-2A with a length of 6.25 (.246); a ferrule section with a length of 2.3 (.091); a total length of 19.7 (.776); a distance of 10 (.394) from the ferrule end to the SMP interface; and a distance of 3.2 (.126) from the ferrule end to the K Jack interface. The SW 5.5 (.217 AF) thread is shown. The end view shows a diameter of 7.14 (Ø.281) and a width of 4.85 (.191) across flats.</p>																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">Parts</th> <th style="width: 25%;">Material</th> <th style="width: 50%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Ferrule</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Body</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Ferrule	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Body	Stainless Steel	Passivated
Parts	Material	Plating (Micro-inch)															
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20															
Insulator	Teflon																
Ferrule	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20															
Body	Stainless Steel	Passivated															
<p>Weight:</p>																	

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.